

LED Surface Mount Light - 38W/74W

Model Number: SML-311-L1/L2



ELECTROPARTS

Technical Data

Features:

- ▶ Die-cast aluminum body
- ▶ UV stabilized powder coated finish
- ▶ UL and CUL listed for wet locations
- ▶ Heat and impact resistant tempered glass
- ▶ DLC listed
- ▶ IC protection
- ▶ Surge protector 10K optional
- ▶ Finish - Bronze

SML-311-L1



7519
lm*

101
lm/W*

75+
Ra

SML-311-L2



*The values for 74W version

Specification

SML-311-L1		SML-311-L2
Optical Information		
Color Temperature	5000K	
Lumen Output (lm)	3605	7519
Beam Angle	120°	
CRI	75+	
Lumen Maintenance (L70)	50,000h	
Environmental Factor		
Starting Temperature	-40°C	
Operating Temperature	-40°C ~ +50°C	
Protection Level	IP65	
Warranty	3 years	
Mechanical Information		
Dimensions (W x H x L)	361mm x 290mm x 235mm	
Weight	6.03kg	
Mounting	Surface Mount	
Electrical Information		
Input Voltage	120-277V	347V
Power Consumption	38W	74W
LED Source	CREE	

LED Surface Mount Light - 38W/74W

Model Number: SML-311-L1/L2



ELECTROPARTS
Technical Data

Dimensions

in mm

